

Pillow Talk

CONDENSED TECHNICAL RIDER



Crew requirements and schedule: (Touring)

- Pre-hung, drapery and electrical test of lighting instruments
- Setup of black dance including stages sides.
- Setup: 4 hours to focus for lighting and video, 4 hours lights, video and sound levels
- Strike: 2 hours including loading the truck

Masking:

Germans On both sides
Italian 4 pairs of black velour legs (opening 30' / 9,14 m), 4 black velour borders, 1 black velour back curtain on center opening traveller.

Stage floor:

Wooden floor (no cement), even without any rake or trip edges. A dance linoleum floor including both stage sides.

Sound specifications:

- 1 pre-installed 3 or 4 way PA speaker system, adequate to properly fill the house, with subwoofers and appropriate amplifiers.
 - 4 stage monitors, on 4 different mixes with equalization
 - 1 digital console min 24 ip, 8 aux, 3 fx (Yamaha LS-9, M7CL, PM5D)
 - 1 professional cd player with auto-pause(ex: Denon, Marantz)
 - 2 microphones SM-58 with stands
 - 1 XLR Snake (32 lines + returns)
 - 3 Clearcoms stations: at controls, US right & DS left.
 - 1 Wireless microphone systems* including 1 head microphone miniature series (ex: Sennheiser HS2, DPA 4065-FR)
- *NB: In case of unacceptable local frequencies of our own wireless microphone systems.

Minimum stage requirements:

Width:

Proscenium: 28 feet / 8,5 m minimum

Wall to wall: 48 feet / 14,7 m (38' / 11,6 m minimum)

Height (stage to hanging pipe):

22 feet / 6,7 m (18' / 5,5 m minimum)

Depth (apron to back wall):

34 feet / 10,4m (30' / 9,14 m minimum)

Crossover: at least 3 feet (1m) wide US of last hanging position



Video requirements:

We are completely self-sufficient in this department.

Lighting specifications:

- 72 dimmers of 2.4Kw each
 - 01 lighting programable board 48/96 with working MIDI at sound mixing position
 - 05 Side lighting booms (Lekos 6x9 or 36 degrees - 1 Kw, with gel frames)
 - 06 Gobo holders for Lekos 6x9 or 36 degrees- 1 Kw
 - 01 FOH : 5 x Leko 36 degrés-Type ETC S4-750w
 - 01 Front Lighting / openingbridge : 5 x Leko 36 degrés-Type ETC S4-750w
 - 02 Back lighting: 5 x Fresnels, 1 Kw with barndoors and gel frames
 - 05 Special lighting: Lekos 6x9 or 36 degrees - 1 Kw, with gel frames
 - 02 SideTIP position PAR 64 Medium / CP62- 1 Kw and gel frames
 - 01 Smoke hazer machine (ex MDG Atmosphere, Antari HZ-500)
- We ask for 8 x XLR -3 lines from controls to our 2 video projectors.